

Table of Contents

1. Introduction and Background	1-1
1.1 Purpose of Manual	1-1
1.2 Purpose of VFS System	1-1
1.3 Application of VFS Systems	1-2
1.4 Definition of VFS System	1-2
1.5 Alternatives to VFS System	1-3
1.5.1 Roof	1-4
1.5.2 VFS System or Equivalent	1-4
1.5.3 Storage and Land Application	1-4
1.5.4 Permanently Vegetated Area	1-4
1.5.5 Alternative Management Options	1-4
1.6 Abbreviations	1-5
1.7 Regulatory Framework	1-5
1.7.1 Legislation	1-5
1.7.2 Approval Process	1-6
1.8 Funding Assistance	1-6
1.9 Best Management Practices/Related OMAFRA Literature	1-7
1.10 Utilization of Professional Design, Engineering, Site Assessment, and Construction Services	1-7
2. General Design Guidance for VFS System Components	2-1
2.1 Description of VFS System Components	2-1
2.1.1 Runoff Collection Area	2-2
2.1.2 Runoff Storage/Settling Basin	2-2
2.1.3 Runoff Collection/Discharge System	2-3
2.1.4 Sump	2-4
2.1.5 Conveyance Pipe	2-5
2.1.6 Distribution Pipe	2-6
2.1.7 Erosion-Proof Pad	2-6
2.1.8 Infiltration Area	2-7

2.2 Assessment of Farmstead Site Conditions Related to Design of VFS System	2-7
2.2.1 Runoff Collection Area Characteristics	2-7
2.2.2 Storage Area Characteristics	2-8
2.2.3 Topographical Relief Characteristics	2-9
2.2.4 Infiltration Area Characteristics	2-9
3. Design Guidelines of VFS System Components	3-1
3.1 Calculate Runoff Quantity	3-1
3.1.1 Establish Extent of Runoff Collection Area Contributing Runoff	3-1
3.1.2 Range in Storage/Settling Basin Volume Requirements	3-1
3.1.3 Defining Runoff Coefficient	3-2
3.1.4 Calculating Runoff Storage/Settling Basin Volume Requirements	3-3
3.2 Design of Storage/Settling Basin	3-4
3.2.1 Integrated Storage/Settling Basin Design	3-4
3.2.2 External Storage/Settling Basin Design	3-7
3.2.3 Emergency Overflow	3-10
3.3 Determination of Discharge Rates from Runoff Storage/Settling Basin	3-10
3.3.1 Discharge from an Integrated Storage/Settling Basin	3-11
3.3.2 Discharge from an External Storage/Settling Basin	3-11
3.4 Runoff Collection/Discharge System	3-12
3.4.1 Integrated Storage/Settling Basin Discharge System	3-12
3.4.2 Integrated Storage/Settling Basin with Direct Discharge to Infiltration Area	3-16
3.4.3 External Settling/Storage Basin Collection/Discharge System	3-16
3.4.4 Calculating Orifice Size Based on Orifice Discharge Capacity	3-18
3.4.5 Perforated Riser Pipe Design	3-19

3.5 Conveyance System	3-19
3.5.1 Conveyance Mechanism	3-27
3.5.2 Open Channel Conveyance	3-27
3.5.3 Managing Flow to Conveyance Pipe	3-29
3.5.4 Design of Conveyance	3-31
3.5.5 Manning's Equation for Establishing Pipe Size	3-33
3.6 Design of Distribution System	3-35
3.6.1 Raised Distribution Pipe	3-35
3.6.2 Design of Raised Distribution Pipe	3-36
3.6.3 Distribution Channel	3-38
3.7 Design of Infiltration Area	3-38
3.7.1 Determining Infiltration Area Size	3-39
3.7.2 Infiltration Area Design Elements	3-47
3.8 Preparation of Design Package	3-52
3.8.1 Engaging Professional Services	3-52
3.8.2 Contents of Design Package	3-52
3.8.3 Specifications	3-53
3.8.4 Construction of VFS System	3-53
3.8.5 Record Keeping	3-53
3.8.6 Inspection	3-54
3.9 Operation and Maintenance	3-54
3.9.1 Runoff Area and Storage (Integrated or External)	3-54
3.9.2 Collection/Discharge Bay	3-55
3.9.3 Pumps	3-55
3.9.4 Piping	3-55
3.9.5 Infiltration Area	3-55
3.9.6 Winter Operation	3-56
3.9.7 Accessibility	3-57
3.9.8 Safety	3-57
3.9.9 VFS System Inspection Sheet	3-57

4. Design Guide	4-1
5. Case Studies	5-1
5.1 Examples and Case Studies	5-1
5.1.1 Design #1 – Design of VFS System (Integrated Storage)	5-1
5.1.2 Design #2 – Design of VFS System (External Storage)	5-9
5.2 Alternative Runoff Treatment	5-16

6. Design Tables	6-1
Table 6.1 Maximum runoff storage/settling volume using conservative method (m ³), 25-year/24-hour storm, holding 100%	6-2
Table 6.2 Minimum storage/settling volume required (m ³) and peak discharge rate (m ³ /s) using rational method, 25-year, 5-minute peak discharge rate	6-18
Table 6.3 Infiltration area required based on saturated hydraulic conductivity of soil texture classes	6-24

Tables

Table 2.1 Evaluation of suitable land to accommodate infiltration area	2-9
Table 3.1 Orifice discharge capacity table	3-20
Table 3.2 Soil texture class and typical hydraulic conductivity under saturated soil conditions	3-40
Table 3.3 Highest monthly precipitation for various Ontario locations	3-44
Table 3.4 15-Minute flow length for 0.0127 m (0.5 in.) flow depth (Manning’s coefficient = 0.24)	3-45

Figures

Figure 1.1 “Before” and “after” schematic	1-3
Figure 2.1 Typical VFS system components	2-1
Figure 2.2 Example of an opportunity and constraints map	2-12
Figure 3.1 Integrated storage/settling basin – containment wall design options	3-5
Figure 3.2 External storage/settling basin profile	3-8
Figure 3.3A Integrated storage/settling basin collection/discharge system layout	3-13

Figure 3.3B Triple angled screen system	3-15
Figure 3.4 Conveyance and distribution channel	3-28
Figure 3.5 Pump/siphon/channel configuration	3-30
Figure 3.6 Raised distribution pipe	3-36
Figure 3.7 Soil horizons	3-41
Figure 3.8 Soil texture by particle-size distribution	3-42

Appendix A – Glossary